

BOREWELL SUBMERSIBLE PUMP SET -125 M.M. (5")

**APPROXIMATE PERFORMANCE DATA AT 2880 RPM, 380-415
VOLTS, THREE PHASE, 50 Hz, A.C. SUPPLY**



Submersible Pump Set

RADIAL FLOW

Pump Model P 75	H.P.	Pump Stage	Out let Size	Cable SQ. M.M.	HEAD IN METER S	DISCHARGE IN LPM						
						0	120	150	180	210	240	270
P-75	3.0	4	2"	1X3X1.5	40	39	37	36	35	33	32	
P-75	4.0	5	2"	1X3X1.5	49	47	45	44	42	40	38	
P-75	5.0	6	2"	1X3X1.5	60	59	57	56	55	53	52	
P-75	6	7	2"	1X3X2.5	70	68	66	65	63	61	59	
Pump Model P 95	H.P.	Pump Stage	Out let Size	Cable SQ. M.M.	HEAD IN METER S	DISCHARGE IN LPM						
						0	180	206	232	258	284	310
P-95	3.0	3	2"	1X3X1.5	30	28	27	25	23	22	20	
P-95	4.0	4	2"	1X3X1.5	36	34	32	31	29	27	25	
P-95	5.0	5	2"	1X3X1.5	45	43	40	38	35	33	30	
P-95	6.0	6	2"	1X3X2.5	56	53	49	46	42	39	35	
P-95	8	8	2"	1X3X2.5	64	60	56	52	48	44	40	

MIXED FLOW

Pump Model P 260	H.P.	Pump Stage	Out let Size	Cable SQ. M.M.	HEAD IN METER S	DISCHARGE IN LPM						
						0	270	294	318	342	366	390
P-260	3.0	3	2.5"	1X3X1.5	26	25	24	23	21	20	19	
P-260	4.0	4	2.5"	1X3X1.5	34	32	31	29	27	26	24	
P-260	5.0	5	2.5"	1X3X1.5	48	46	44	42	39	37	35	
P-260	6.0	6	2.5"	1X3X2.5	58	55	53	50	47	45	42	
P-260	7.5	7	2.5"	1X3X2.5	66	63	61	58	55	53	50	